


IP20 - MAINTAINED / NON-MAINTAINED **EMERGENCY LED EXIT BOX**

SKU:S30628



INFORMATION

Modern LED emergency light test button. An essential safety feature for any commercial environment. The Exit box is designed for simple wall mounting. Exit box is pre-installed with an UP directional arrow legend, other legends are available separately.

Warranty: 5 Years


Legends: S30760 = Arrow Left

S30761 = Arrow Right S30762 = Arrow Down



SPECIFICATIONS

\bigoplus	Wattage	2W
4	Voltage	220-240V (AC)
√ √	Frequency	50/60Hz
THE	Lumen Output Mains	45lm
THE	Emergency Lumen Output	40lm
640	Viewing Distance	24m
Q.	Test Button	Yes
	Operating Temperature	0-40°C
- +	Battery Type	LiFePO4 18650 3.2V 1,000mAh
	Charging Time	24hours
<u>-</u> ^-	Emergency Duration	3hours
	Colour Temperature	6,500K (Daylight)
	Weight	604g
	IP Rating	IP20
	Safety Class	Class 1



320mm

26mm

Installation hole N/A

0

LK C € ≈ RoHS Compliant

Cable entry hole 20mm

LUMiLife is constantly developing and improving its products. For this reason, all product descriptions are intended as a general guide and we may change specifications time to time in the interest of product development, without prior notification or public announcement. Data in this sheet has been obtained in controlled experimental conditions. However, LUMiLife cannot accept any liability arising from the reliance on such data to the extent permitted by law. NOTE: PowerMaster is transitioning to LumiLife, during this time

current stock may be delivered as PowerMaster.









