LUMiLife

36W LED TPA BACKLIT PANEL LIGH

600 x 600 x 34mm | TP(a)

SKU: S16731 - PB6X636WU194K S16372 - PB6X636WU195K S16733 - PB6X636WU196K

INFORMATION

UGR < 19

Measuring 595mm x 595mm x 34mm, this new LUMiLiFe 36W Backlit LED panel (UGR<19) light typically replaces 4 x 600mm T8/T5 fluorescent tubes lights set in 600 x 600 grids. Which is why they're the popular lighting choice for hotels, factories, offices, schools, colleges, hospitals and the like. Energy use will be reduced by up to 50% and you'll notcie a dramatic improvement in light quality.

FEATURES

- Lumens: 3600 + / 5%
- Beam angle: 80 Degrees
- Life span: 50,000Hrs
- IP Rating: IP20
- CE & RoHS Certified
- Uniform Light Distribution
- TP(a)
- Non-Flicker Driver
- Unified Glare Rating (UGR): <19*</p>

*this panel allows the installation to comply with EN12464

TECHNICAL PARAMETER

- Input: AC 220-240V 50/60Hz 900mA $\rightarrow 27-42V$
- Output Current: DC 30-42V
- LED Type: SMD
- Output Power: 36W
- Lens Material: PMMA
- Diffuser Material: PS + PS
- Sanan LED SMD Chip 2835

APPLICATIONS

- Hotels
- Conference/Meeting rooms
- Factories and offices
- Schools, colleges, universities and hospitals









LUMiLife is constantly developing and improving its products. For this reason, all product descriptions are intended as a general guide and we may change specifications time to time in the interest of product development, without prior notification or public announcement. Data in this sheet has been obtained in controlled experimental conditions. However, LUMiLife cannot accept any liability arising from the reliance on such data to the extent permitted by law.



Unit 4 Beacon Road | Ashburton Road West Trafford Park | Manchester | M17 1AF



LUMiLife


36W LED BACKLIT PANEL LIGHT UGR < 19 600 x 600 x 34mm | TP(a)

SKU: S16731 - PB6X636WU194K, S16372 - PB6X636WU195K, S16733 - PB6X636WU196K

SPECIFICATIONS

Model#	сст	LED Type	Lumen (Lm) (±5%)	CRI	Beam Angle	Voltage (V)	PF	Weight (kg)
S16731 PB6X636WU194K	4,000K	SMD	3,600Lm	>80	80°	AC 220-240V	>0.9	1.7
S16732 PB6X636WU195K	5,000K	SMD	3,600Lm	>80	80°	AC 220-240V	>0.9	1.7
S16733 PB6X636WU196K	6,500K	SMD	3,600Lm	>80	80°	AC 220-240V	>0.9	1.7

DIMENSIONS (mm)



All dimension tolerances are ±0.5mm unless otherwise stated.

ACCESSORIES

- Hanging Kit for suspended installation
- Spring Clips
- Surface Mounted Clips
- External 3hr Emergency Pack (UK Manufactured)-

